Summary of Shimming Results in 21Q40 Quadrupoles


Animesh Jain
Superconducting Magnet Division, BNL

Updated: June 16, 2003


Shimming Results in 21Q40

- One quad with 1 mil stainless steel shims (Sl. No. 14)
- Stainless steel shims significantly reduce the I.T.F. !!
- Sl. No. 14 re-shimmed with 1 mil iron shims.
- Seven quads with 1 mil iron shims (# 2, 3, 14, 15, 16, 20, 23)
- # 15 re-shimmed with additional 1 mil iron shim (2 mil total).
- Sl. No. 2 and 3 were measured without shims early in the program, before power supply was repaired.
- # 2 and 3 results are significantly different from the remaining quadrupoles (# 14,15_(1),16,20,23), but similar to # 15_(2).
- Results for 940 A cycle agree with those for 450 A cycle, except for Sl. No. 20, where results disagree by ~0.02%.
- Including all results, the average change in I.T.F. at 700A for 1 mil shim is 0.036%, with an RMS variation of 0.02%.


SQ2114: Effect of 1 mil S.S. Shims Under Poles




SQ2114:Before shimming Vs after shims removed




SQ2114: Effect of 1 mil Iron Shims Under Poles




SQ2114: Effect of 1 mil Iron Shims Under Poles




SQ2102: Effect of 1 mil Iron Shims Under Poles




SQ2103: Effect of 1 mil Iron Shims Under Poles




SQ2115: Effect of First 1 mil Iron Shims Under Poles




SQ2115: Effect of 1 mil Additional Iron Shims Under Poles




SQ2116: Effect of 1 mil Iron Shims Under Poles





SQ2120: Effect of 1 mil Iron Shims Under Poles





SQ2123: Effect of 1 mil Iron Shims Under Poles


















21Q40; 1.0 GeV Group Trends



21Q40; 1.3 GeV Group Trends

